


# Wireless interface

Dry contact with 12-24Vdc/ac power supply




## PLANO-LOCK

Control unit with dry contact function. 12/24 Vac/dc power supply. 1 output with normally open contact. Radio receiver 433.92MHz. Integrated WiFi module for remote control by App OneSmart and voice command. 1 limit switch input for controlling the state of the device (e.g. Closed/Opened door in gate-door automation application)




Code	PLANO-LOCK
Power supply	12 Vdc or 230Vac
Output	1 NO contact max 1A (START function) 1 NC contact max 1A (STOP function)
Input	2 settable input (NO/NC) with "gate status" function
Function	Impulse
No. Programmable transmitters	80
Radio frequency	433.920 MHz ISM
Wireless Smart	WiFi 2,4GHz
Smart remote control	App OneSmart
Voice commands	Google home - Alexa Amazon
Protection rating	IP20
Working temperature	-20 +55 °C
Dimensions	80x80x16

## ACCESSORIES FOR PLANO-LOCK



### Lock-Switch 12

Automation status reporting accessory on OneSmart  
Connection to gate/port light 12Vdc.  
Dimensions: Ø35mm x 15mm



### Lock-Switch 24

Automation status reporting accessory on OneSmart  
Connection to gate/port light 24Vdc.  
Dimensions: Ø35mm x 15mm

## SERIE PLANO

